Serial No.: 10/043,712 Filed: January 8, 2002

Page : 2 of 25

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) A computer_implemented method for predicting failure in a system, the method comprising:

measuring receiving data associated with a system, the received data including sensed data indicative of a system response to a specific load on the system while the system is in operation other than undergoing a system test;

ereating calculating a prediction indicative of a potential failure of said system using a pre-selected physics based probabilistic model and said received data, the physics based probabilistic model selected to calculate said prediction based on at least the specific load; and communicating said prediction.

- 2. (Original) The method of claim 1, wherein said measuring further comprises receiving system information from said system.
- 3. (Currently Amended) The method of claim 1, wherein said ereating calculating a prediction further comprises ereating calculating a prediction of a failure of a component of said system.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 3 of 25

4. (Currently Amended) The method of claim 1, wherein said ereating calculating a prediction further comprises ereating calculating a prediction of a failure of multiple systems based on said prediction.

- 5. (Currently Amended) The method of claim 1, wherein said measuring and ereating steps are performed on said systemthe data indicative of a system response to a specific load comprises a bend angle, and wherein creating a prediction indicative of a potential failure of said system using a physics based probabilistic model and said received data comprises using the bend angle and the physics based probabilistic model to generate a response surface.
- 6. (Previously Presented) The method of claim 1, further comprising comparing said prediction to criteria.
- 7. (Currently Amended) The method of claim 1, wherein at least one of said ereating calculating and communicating steps occurs at a location remote from said system.
- 8. (Currently amended) The method of claim 1, wherein said physics based probabilistic model comprises multiple <u>pre-selected</u> physics based probabilistic models, <u>wherein</u> at least one of the multiple <u>pre-selected</u> physics based probabilistic models is selected to <u>calculate the prediction based on the one or more pre-determined failure modes of the system.</u>
- 9. (Previously Presented) The method of claim 1, further comprising ranking variables in said physics based probabilistic model according to said variable's contribution to said prediction.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 4 of 25

steps.

10. (Original) The method of claim 1, applied to predict failure in a material's microstructure.

- 11. (Currently Amended) The method of claim 1, wherein said <u>received</u> data <u>further</u> comprises referred data, sensed data, and inferred data and wherein said method further comprises relating said referred data to a first set of variables, relating said sensed data to a second set of variables, and inferring a third set of variables from said sensed data.
- 12. (Currently Amended) The method of claim 1, further comprising sending <u>at</u> <u>least some of said received</u> data to a remote location and wherein said <u>creating calculating said</u> prediction occurs at said remote location.
- 13. (Original) The method of claim 12, further comprising receiving said prediction from said remote location.
- 14. (Currently Amended) The method of claim 1, further comprising developing said physics based probabilistic model prior to said ereating calculating said prediction.
- 15. (Previously Presented) The method of claim 14, wherein said developing further comprises:

identifying at least one failure mechanism of a component of said system from said component's characteristics selected from the group consisting of: material properties, environmental conditions, design characteristics, component loading, and component usage;

identifying significant random variables of said at least one failure mechanism; identifying statistical parameters of said significant random variables; and formulating a strategy for physics based probabilistic analysis based on said identifying

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 5 of 25

16. (Currently Amended) The method of claim 15, wherein said <u>received</u> data <u>further</u> comprises referred data, sensed data, and inferred data and wherein said developing step further comprises determining which of said significant random variables are related to said referred data, which of said significant random variables are related to said sensed data, and which of said significant random variables are inferred from said sensed data.

- 17. (Original) The method of claim 12, wherein said developing further comprises setting criteria for communicating said prediction.
- 18. (Previously Presented) The method of claim 1, wherein said physics based probabilistic model utilizes fast probability methods.
- 19. (Previously Presented) The method of claim 18, wherein said fast probability methods are direct fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.
- 20. (Previously Presented) The method of claim 18, wherein said fast probability methods are response surface fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.
- 21. (Previously Presented) The method of claim 1, wherein said physics based probabilistic model utilizes simulation techniques.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 6 of 25

22. (Previously Presented) The method of claim 21, wherein said simulation techniques are direct methods selected from the group consisting of: Monte Carlo methods and importance sampling methods.

- 23. (Previously Presented) The method of claim 21, wherein said simulation techniques are response surface methods selected from the group consisting of: Monte Carlo methods and importance sampling methods.
- 24. (Original) The method of claim 15, wherein at least one said failure mechanism is described by an equation and said equation is divided into a capacity section and a demand section.
- 25. (Currently Amended) An apparatus for predicting failure of monitoring a system, said apparatus comprising:

sensors for acquiring <u>sensed</u> data <u>indicative of a current physical state</u> from <u>of</u> a particular system;

one or more data processing systems including a first computer comprising:

a processor; and

a memory comprising:

instructions for measuring receiving data including said acquired data;

instructions for ereating a prediction of a failure determining a current operation status of said particular system using a physics based probabilistic model to determine the current operation status based on a probable response of the particular system to one or more external parameters at a current time, and further using said acquired data; and

instructions for communicating said prediction current operation status; and

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 7 of 25

a communication device for communicating said prediction current operation status.

- 26. (Currently Amended) The apparatus of claim 25, wherein said instructions for ereating determining the current operation status further comprise instructions for predicting failure determining a probable response of at least one component of said system to the one or more external parameters at the current time.
- 27. (Currently Amended) The apparatus of claim 256, wherein said instructions for measuring further comprise instructions for receiving system information from said system said instructions for determining a probable response of said at least one component of said system to the one or more external parameters at the current time comprises instructions for performing finite element analysis using at least a component configuration and data indicative of the one or more external parameters at the current time.
- 28. (Currently Amended) The apparatus of claim 27, wherein the one or more data processing systems further comprise instructions for determining a future operation status of said particular system using the physics based probabilistic model further comprising a second computer, said second computer comprising:

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 8 of 25

29. (Currently Amended) The apparatus of claim 25, the data processing system further comprising:

a second computer, said second computer comprising:

a processor; and

a memory, said memory comprising:

instructions for receiving said prediction current operation status; and instructions for communicating said prediction current operation status; and a second communication device for communicating said prediction current

operation status.

- 30. (Original) The apparatus of claim 25, wherein said communication device further comprises a warning signal.
- 31. (Currently Amended) The apparatus of claim 25, said apparatus further comprising a sending device for sending <u>at least some of said received</u> data to a location remote from said system.
- 32. (Previously Presented) The apparatus of claim 31, wherein said first computer is located remote from said system.
- 33. (Currently Amended) The apparatus of claim 25, further comprising instructions for comparing said prediction current operation status to criteria.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 9 of 25

34. (Previously Presented) The apparatus of claim 25, wherein said physics based probabilistic model comprises multiple models.

- 35. (Currently Amended) The apparatus of claim 25, wherein said physics based probabilistic model comprises variables ranked according to said variables' contribution to said prediction current operation status.
- 36. (Original) The apparatus of claim 25, applied to predict failure in a material's microstructure.
- 37. (Currently Amended) The apparatus of claim 25, wherein said <u>received</u> data <u>further</u> comprises referred data, sensed data, and inferred data and wherein said apparatus further comprises instructions for:

relating said referred data to a first set of variables; relating said sensed acquired data to a second set of variables; and inferring a third set of variables from said sensed acquired data.

- 38. (Previously Presented) The apparatus of claim 25, wherein said physics based probabilistic model utilizes fast probability methods.
- 39. (Previously Presented) The apparatus of claim 38, wherein said fast probability methods are direct fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 10 of 25

40. (Previously Presented) The apparatus of claim 38, wherein said fast probability methods are response surface fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.

- 41. (Previously Presented) The apparatus of claim 25, wherein said physics based probabilistic model utilizes simulation techniques.
- 42. (Previously Presented) The apparatus of claim 41, wherein said simulation techniques are direct methods selected from the group consisting of: Monte Carlo methods; and importance sampling methods.
- 43. (Previously Presented) The apparatus of claim 41, wherein said simulation techniques are response surface methods selected from the group consisting of: Monte Carlo methods; and importance sampling methods.
- 44. (Original) The apparatus of claim 25, wherein said instructions for creating further comprise instructions for creating a prediction of a failure of multiple systems based on said prediction.
- 45. (Currently Amended) The apparatus of claim 25, said physics based probabilistic model <u>is pre-selected based on comprising</u> at least one failure mechanism of a component of said system.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 11 of 25

46. (Currently Amended) The apparatus of claim <u>245</u>, wherein said at least one failure mechanism relates to a material microstructure.

- 47. (Original) The apparatus of claim 25, wherein said at least one failure mechanism is described by an equation and said equation is divided into a capacity section and a demand section.
- 48. (Currently Amended) A computer program product for predicting failure of a system for use in conjunction with a computer system, said computer program product comprising:

a computer readable storage medium and a computer program mechanism embedded therein, said computer program mechanism comprising:

instructions for measuring receiving data including sensed data indicative of a current physical state;

instructions for storing said data;

instructions for ereating a prediction of failure determining a failure probability of said system using a physics based probabilistic model and said data, the physics based probabilistic model to determine the failure probability based on modeling a response of the system to at least one force; and

instructions for communicating <u>data indicative of said determined failure</u> <u>probability said prediction</u>.

49. (Currently Amended) The computer program product of claim 48, wherein the instructions for determining the failure probability of the system further comprise instructions for

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 12 of 25

determining a probable response of at least one component of said system to the at least one force said instructions for measuring data further comprise instructions for receiving system information from said system.

- 50. (Currently Amended) The computer program product of claim 48, wherein said instructions for determining the probable response of at least one component of the system to the at least one force comprise instructions for performing finite element analysis using at least a component configuration and data indicative of the at least one forcesaid instructions for creating further comprise instructions for creating a prediction of a failure of at least one component of said system.
- 51. (Currently Amended) The computer program product of claim 48, wherein said instructions for ereating determining a failure probability further comprise instructions for ereating a prediction of a failure determining a failure probability of multiple systems based on said sensed data indicative of the current physical stateprediction.
- 52. (Currently Amended) The computer program product of claim 48, said physics based probabilistic model comprising is pre-selected based on at least one predetermined failure mechanism of a component of said system.
- 53.(Currently Amended) The computer program product of claim 48, wherein said at least one <u>pre-determined</u> failure mechanism relates to a material microstructure.
- 54. (Currently Amended) The computer program product of claim 48, wherein said at least one <u>pre-determined</u> failure mechanism is described by an equation and said equation is divided into a capacity section and a demand section.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 13 of 25

55. (Currently Amended) The computer program product of claim 48, further comprising instructions for comparing said prediction failure probability to criteria.

- 56. (Previously Presented) The computer program product of claim 48 wherein said physics based probabilistic model comprises multiple physics based probabilistic models.
- 57. (Currently Amended) The computer program product of claim 48, further comprising ranking variables in said physics based probabilistic model according to said variables' contribution to said <u>prediction failure probability</u>.
- 58. (Original) The computer program product of claim 48, applied to predict failure in a material's microstructure.
- 59. (Currently Amended) The computer program product of claim 48, wherein said <u>received</u> data <u>further</u> comprises:

referred data; and

sensed data; and

inferred data and wherein said apparatus further comprises:

instructions for relating said referred data to a first set of variables; instructions for relating said sensed data to a second set of variables; and instructions for inferring a third set of variables from said sensed data.

60. (Previously Presented) The computer program product of claim 48, wherein said physics based probabilistic model utilizes fast probability methods.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 14 of 25

61. (Previously Presented) The computer program product of claim 60, wherein said fast probability methods are direct fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.

- 62. (Previously Presented) The computer program product of claim 60, wherein said fast probability methods are response surface fast probability methods selected from the group consisting of: First Order Reliability Methods, Second Order Reliability Methods, Advanced Mean Value methods, and Mean Value methods.
- 63. (Previously Presented) The computer program product of claim 48, wherein said physics based probabilistic model utilizes simulation techniques.
- 64. (Previously Presented) The computer program product of claim 63, wherein said simulation techniques are direct methods selected from the group consisting of: Monte Carlo methods, and importance sampling methods.
- 65. (Previously Presented) The computer program product of claim 63, wherein said simulation techniques are response surface methods selected from the group consisting of: Monte Carlo methods, and importance sampling methods.
- 66. (Currently Amended) The computer program product of claim 49, further comprising:

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 15 of 25

instructions for determining a future failure probability of said system using the physics based probabilistic modela second computer program product, said second computer program product comprising:

a second computer readable storage medium and a second computer program mechanism embedded therein, said-second computer program mechanism comprising:

instructions for measuring said data;

instructions for storing said data; and

instructions for sending said data to said first computer as said system

information.

67. (Currently Amended) The computer program product of claim 48, further comprising:

a second computer program product, said second computer program product comprising:

a second computer readable storage medium and a second computer program mechanism embedded therein, said second computer program mechanism comprising:

instructions for receiving said prediction failure probability; and instructions for communicating said prediction failure probability.

68. (Currently Amended) A computer_implemented method for predicting failure in a system, the method comprising:

determining failure mechanisms for a system;

measuring receiving data associated with the system while the system is in operation other than undergoing system test;

during system operation, ascertaining a probability of failure for each of said a plurality of pre-determined failure mechanisms using a physics based first probabilistic failure model, wherein said probability of failure for each of said failure mechanisms is based at least partially on said received data and said pre-determined failure mechanisms;

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 16 of 25

predicting a probability of failure for the system using a physics based second probabilistic failure model, wherein said probability of failure for the system is at least partially based on said probability of failure of said failure mechanisms; and communicating the probability of failure of the system.

69. (Previously Presented) The method of claim 68, further comprising, before said ascertaining, determining one or more suitable physics based probabilistic failure models for each failure mechanism.

70. (Previously Presented) The method of claim 68, wherein said failure mechanisms are selected from the group consisting of: cracking, delamination, shearing, bending, and tension fracture.

- 71. (Previously Presented) The method of claim 68, wherein said failure mechanisms are selected from the group consisting of: material properties, environmental conditions, design characteristics, component loading, and component usage.
- 72. (Previously Presented) The method of claim 68, wherein said probability of failure for each of said failure mechanisms is further based on variability of physical parameters of said system.
- 73. (Previously Presented) The method of claim 68, wherein said probability of failure for each of said failure mechanisms is further based on a variability of directly sensed variables, a variability of referred variables, and a variability of inferred variables.

Serial No.: 10/043,712 Filed: January 8, 2002

Page : 17 of 25

74. (Currently Amended) A computer implemented method for predicting failure in a system, comprising:

determining failure mechanisms for a system;

measuring receiving data associated with the system while the system is in operation other than undergoing system test;

selecting at least one suitable physics based probabilistic failure model for each failure mechanism;

ascertaining a probability of failure for each of said failure mechanisms using a <u>selected</u> physics based first probabilistic failure model, wherein said probability of failure for each of said failure mechanisms is based at least partially on said <u>received</u> data, said failure mechanisms, and variability of physical parameters of said system;

predicting a probability of failure for the system using a <u>selected</u> physics based second probabilistic failure model, wherein said probability of failure for the system is at least partially based on said probability of failure for each of said failure mechanisms; and communicating said probability of failure for the system.

75. (Previously Presented) The method of claim 74, wherein said variability of physical parameters comprises a variability of directly sensed variables, a variability of referred variables, and a variability of inferred determined variables.

76. (Previously Presented) The method of claim 74, further comprising, before said communicating, determining a confidence of said probability of failure of said system based on historical failure data.